# **OSRAM**

# BATTERYjumpstart 1500



#### Starts completely depleted batteries

New Boost function allows user to restart vehicles with depleted batteries



#### **Powerful Lithium Battery**

Starts up to 6-liter petrol and 3-liter diesel vehicles



#### **PD60W Power Pack**

Fast charges phones and other devices via the built in USB ports



# Powerful and safe jumpstarting for 12V vehicles with integrated USB charging and enhanced safety features

The OSRAM BATTERYjumpstart 1500 can jump-start vehicles with engines up to 6L Petrol or 3L Diesel. With 1500A starting power, it is suitable for most 12V cars, vans, SUVs, and LCVs. The boost function enables jump-starting of completely depleted batteries. The unique ergonomic smart clamp connection features longer cables for better accessibility in hard-to-reach areas. Safety features include reverse polarity protection, anti-spike protection, and short circuit protection, with audible and LED indicators. An integrated torch illuminates the work area, and LED indicators show the current battery level. The unit features PD60W fast charge technology for rapid recharging and powerful charging of mobile devices via the USB C and USB A ports.

# Product datasheet

#### Technical data

# **Product information**

Application (Category and Product specific)	Lithium Starter	
Recommended Petrol Engine size (up to)	6 l	
Recommended Diesel Engine size (up to)	3 (	


### **General Product Information**

Global order reference	OJS030
------------------------	--------

### **Electrical Data**

Cranking Amps	350
Peak Amps	1500
Boost-Function (start batteries from 0V)	Yes

# **Physical Attributes & Dimensions**



Length	254.0 mm
Width	42.0 mm
Height	94.0 mm

# Additional product data

Type of Battery	Lithium Ion
Battery Capacity	12000 mAh
Charging Type	USB-C
Charging time	1 hr
Power bank function	Yes

# **Environmental & Regulatory Information**

### Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Candidate list substance 1	Lead			
CAS No. of substance 1	7439-92-1			
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.			
Declaration no. in SCIP database	29b37b89-8a00-4a8c-bc7f-646af72bcd86			

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172408233	BATTERYjumpstart 1500	Folding carton box 1	214 mm x 132 mm x 96 mm	2.71 dm³	1146.00 g
4062172408240	BATTERYjumpstart 1500	Shipping carton box 4	282 mm x 232 mm x 224 mm	14.65 dm³	4944.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Download Data

File



Brochures
BATTERYjumpstart 1500 Lithium Starter

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

